

Kanlux

AREAS OF APPLICATION

- OFFICES ► ILLUMINATING OF SHOPS
- WAREHOUSES ► UNDERGROUND PARKING
- PUBLIC BUILDINGS
- SOCIAL AND TECHNICAL ROOMS

IQ-LED EX T8

index	article	power	luminous flux	EEi	Length
35254	IQ-LED EX T8 12W-NW	12W	2520lm	A+G A	1212mm

T8 LED GLASSv5

index	article	power	luminous flux	EEi	Length
33216	T8 LED GLASSv5 12W-NW	12W	2220lm	A+G B	1212mm
33217	T8 LED GLASSv5 12W-CW	12W	2220lm		

T8 LED GLASSv4

index	article	power	luminous flux	EEi	Length
33210	T8 LED GLASSv4 9W-NW	9W	1440lm	A+G C	602mm
33211	T8 LED GLASSv4 9W-CW	9W	1440lm		
33212	T8 LED GLASSv4 18W-NW	18W	2880lm		1212mm
33213	T8 LED GLASSv4 18W-CW	18W	2880lm		
33218	T8 LED GLASSv4 22W-NW	22W	3520lm		1512mm
33219	T8 LED GLASSv4 22W-CW	22W	3520lm		

T8 LED GLASSv3

index	article	power	luminous flux	EEi	Length
26062	T8 LED GLASSv3 9W-NW	9W	1350lm	A+G D	600mm
26063	T8 LED GLASSv3 9W-CW	9W	1260lm		
26064	T8 LED GLASSv3 18W-NW	18W	2700lm		1210mm
26065	T8 LED GLASSv3 18W-CW	18W	2700lm		
26058	T8 LED GLASSv3 22W-NW	22W	3080lm		1512mm
26059	T8 LED GLASSv3 22W-CW	22W	3080lm		

T8 LED

index	article	power	luminous flux	EEi	Length
37630	T8 LED 9-NW	9W	900lm	A+G F	600
37631	T8 LED 9-CW	9W	900lm		
37632	T8 LED 18-NW	18W	1820lm		1210
37633	T8 LED 18-CW	18W	1820lm		
37634	T8 LED 22-NW	22W	2270lm		1512
37635	T8 LED 22-CW	22W	2270lm		

Colour Temperature: NW 4000K; CW 6500K, rated voltage: 220-240V

Kanlux

T8 LED TUBES

A wide range
for professional use

kanlux.com

TUBY T8 LED



HIGH
PF>0,9



	T8 LED			T8 LED GLASSv3			T8 LED GLASSv4			T8 LED GLASSv5	IQ-LED EX T8
											
	Kanlux			Kanlux			Kanlux			Kanlux	iQ-LED Kanlux
efficacy	100lm/W			do 150lm/W			160lm/W			185lm/W	210lm/W
power	9W	18W	22W	9W	18W	22W	9W	18W	22W	12W	12W
luminous flux Φuse [lm]	900	1820	2270	to 1350	to 2700	to 3300	1440	2880	3520	2220	2520
light colour	NW 4000K, CW 6500K			NW 4000K, CW 6500K			NW 4000K, CW 6500K			NW 4000K, CW 6500K	NW 4000K
durability	20 000h			do 30 000h			30 000h			40 000h	50 000h
EEI											
beam angle	200°			do 250°			220°			200°	200°
PF	>0,5			>0,5			>0,9			>0,9	>0,9
ON/ OFF cycles	≥20000			≥15 000 - 25 000			≥30 000			≥50 000	≥50 000
shade	milk			milk			milk			milk	milk
* warranty	2 years			to 3 years			3 years			4 years	5 years



kanlux.com

* Extended warranty is subject to the terms of the warranty statement available on the website.