



Two-screw pipe clamp INOX AISI 304, AISI 316

Objímka dvoušroubová nerezová A2, A4

TDS315


Stainless steel V2A
Nerezová ocel
třídy AISI 304

Stainless steel V4A
Nerezová ocel
třídy AISI 316

Vlastnosti a výhody

- Materiál: nerezová ocel
- Dvoudílná konstrukce se dvěma uzavíracími šrouby – rovnoměrné sevření a lepší přizpůsobení průměru potrubí
- Vyrobeny z nerezové oceli pro prostředí s vysokými požadavky na odolnost proti korozi
- Speciální tlumicí vložka z EPDM pryže
- Teplotní odolnost vložky od -50 °C do +110 °C
- **Použití:** univerzální použití, běžně používané druhy potrubí:
 - ocelové,
 - plastové,
 - litinové,
 - meděné,
 - nerezové.

Features and benefits



- Material: stainless steel
- Two-piece design with two locking screws – ensures even clamping and better adaptation to pipe diameters
- Made of stainless steel for environments with high corrosion resistance requirements
- Special damping insert made of EPDM rubber
- Insert temperature resistance from -50 °C to +110 °C
- **Application:** universal use; commonly used pipe types:
 - steel,
 - plastic,
 - cast iron,
 - copper,
 - stainless steel.

Obj. číslo A2 Ord. code V2A	Obj. číslo A4 Ord. code V2A	Průměr Diameter			Matice Nut M	Délka Length L [mm]	Šířka × tloušťka Width × thickness S × t [mm]	Max. dovolené zatížení Max. safe load Fa, z [N]	Balení Package ks / pcs
		Ø D [mm]	D" [in]	DN					
315001216	315101216	12 – 16	1/4"	8	M8	56	20 × 1,2	800	100
315001719	315101719	17 – 19	3/8"	10	M8	59	20 × 1,2	800	100
315002023	315102023	20 – 25	1/2"	15	M8	62	20 × 1,2	800	100
315002530	315102530	26 – 30	3/4"	20	M8	68	20 × 1,2	800	100
315003138	315103138	31 – 38	1"	25	M8	78	20 × 1,2	800	100
315004046	315104046	40 – 46	5/4"	32	M8	88	20 × 1,2	800	100
315004853	315104853	48 – 53	6/4"	40	M8	96	20 × 1,2	800	50
315005459	315105459	54 – 59	-	-	M8	101	20 × 1,2	800	50
315006064	315106064	60 – 64	2"	50	M8	111	20 × 1,2	800	50
315006771	315106771	67 – 71	-	-	M8	116	20 × 1,2	800	50
315007278	315107278	72 – 78	2 1/2"	65	M10	127	25 × 1,5	2500	50
315008186	315108186	81 – 86	-	-	M10	138	25 × 1,5	2500	50
315008792	315108792	87 – 92	3"	80	M10	145	25 × 1,5	2500	50
315009510	315109510	95 – 103	-	-	M10	156	25 × 1,5	2500	50
315101106	315111106	102 – 116	4"	100	M10	170	25 × 2,0	2500	50
315101121	315112112	121 – 127	-	-	M10	185	25 × 2,0	2500	25
315101133	315113942	133 – 141	5"	125	M10	201	25 × 2,0	2500	25
315101159	315116468	159 – 168	6"	150	M10	230	25 × 2,0	2500	25

Two-screw pipe clamp INOX AISI 304, AISI 316

Objímka dvoušroubová nerezová A2, A4

TDS315


Stainless steel V2A
Nerezová ocel
třídy AISI 304

Stainless steel V4A
Nerezová ocel
třídy AISI 316

Obj. číslo A2 Ord. code V2A	Obj. číslo A4 Ord. code V2A	Průměr Diameter			Matice Nut M	Délka Length L [mm]	Šířka × tloušťka Width × thickness S × t [mm]	Max. dovolené zatížení Max. safe load Fa, z [N]	Balení Package ks / pcs
Ø D [mm]	D" [in]	DN							
3G5001519	3G6001719	15 - 19	3/8"	10	M8/M10	59	20 × 1,2	800	100
3G5002023	3G6002023	20 - 25	1/2"	15	M8/M10	62	20 × 1,2	800	100
3G5002530	3G6002530	26 - 30	3/4"	20	M8/M10	68	20 × 1,2	800	100
3G5003138	3G6003138	31 - 38	1"	25	M8/M10	78	20 × 1,2	800	100
3G5004046	3G6004046	40 - 46	5/4"	32	M8/M10	88	20 × 1,2	800	100
3G5004853	3G6004853	48 - 54	6/4"	40	M8/M10	96	20 × 1,2	800	50
3G5005459	3G6005459	54 - 59	-	-	M8/M10	101	20 × 1,2	800	50
3G5006064	3G6006064	60 - 64	2"	50	M8/M10	111	20 × 1,2	800	50
3G5006771	3G6006771	67 - 71	-	-	M8/M10	116	20 × 1,2	800	50
3G5007278	3G6007278	72 - 78	2 1/2"	65	M8/M10	127	25 × 1,5	2500	50
3G5008792	3G6008792	87 - 92	3"	80	M8/M10	145	25 × 1,5	2500	50
3G5009510	3G6009510	95 - 103	-	-	M8/M10	156	25 × 1,5	2500	50
3G5101116	3G6101116	102 - 116	4"	100	M8/M10	170	25 × 2,0	2500	50

